



SPECIFICATIONS:

VOLTAGE RANGE - - - - - 150-280VAC  
 FREQUENCY - - - - - 45-65 Hz  
 PHASE/WIRE - - - - - SINGLE, LINE + NEUTRAL + GROUND  
 VOLTAGE REGULATION - - - - - ±2%  
 RATED POWER FACTOR - - - - - 0.7 LAGGING  
 HOT SWAP BATTERIES - - - - - YES

LISTED UL1778;CE-FCC CLASS A  
 UL FILE NO.: E191175

LOCKABLE SWIVEL CASTORS (4)

MODEL #	DIM. "A"	VOLTAGE	WEIGHT LBS.	CAPACITY	BATTERY RUN TIME @ FULL LOAD	TYPE	RECHARGE TIME
SC60021T	29.50 [749.3]	208/220/230/240VAC SELECTABLE, 240/120, 208/120VAC	265	6000VA/4200W	8 MINIUTES	SEALED LEAD ACID MAINTENANCE FREE, 20 EACH 12V/7AH, 240Vdc	4 HOURS @ 90%
SC60022T	29.50 [749.3]	208/220/230/240VAC SELECTABLE	190				
SC80021T	34.69 [881.1]	208/220/230/240VAC SELECTABLE, 240/120, 208/120VAC	320	8000VA/5600W	7 MINUTES	SEALED LEAD ACID MAINTENANCE FREE, 20 EACH 12V/9AH, 240Vdc	5 HOURS @ 90%
SC80022T	29.50 [749.3]	208/220/230/240VAC SELECTABLE	203				
SC11021T	34.69 [881.1]	208/220/230/240VAC SELECTABLE, 240/120, 208/120VAC	340	10000VA/7000W	5 MINUTES	SEALED LEAD ACID MAINTENANCE FREE, 20 EACH 12V/9AH, 240Vdc	
SC11022T	29.50 [749.3]	208/220/230/240VAC SELECTABLE	223				

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ± DECIMALS .010 XX .010 XXX .005		HOLES .005	ANGLES 1*	DRAFT 1-1/2*	UNITS IN [mm]	TITLE: SPEC. CONTROL DRAWING UNINTERRUPTIBLE POWER SUPPLY UNISTAR P SERIES		 <small>A Corporation of America Company 201 Dallas Boulevard Dallas, TX 75242 USA</small>	
MATERIAL:		ALL DIMENSIONS APPLY AFTER PLATING		DRAWN BY T.SNAY		DATE 4/28/09	FIRST USED ON	DO NOT SCALE DWG.	
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.				CHECKER S.A.SMITH		DATE 4/28/09	WEIGHT APPROX. 83008	CAGE CODE 83008	DWG. NO. 096-4302
				ENGINEER S.A.SMITH		DATE 4/28/09	SCALE	SHEET 1 OF 1	